

# RUUD SALES FACT SHEET

**R92P- SERIES**  
**92% A.F.U.E.†**  
**Models with Input Rates of**  
**40 to 115 kBTU**  
**[11.72 to 33.71 kW]**



## Ruud Achiever® Series Multi position Gas Furnaces

### Features

- 92% residential gas furnace CSA certified
- 4 way multi-raise design
- PlusOne™ Diagnostics 7-Segment LED all units
- PlusOne™ Ignition System – DSI for reliability and longevity
- PlusOne™ Water Management System with patented Blocked Drain Sensor
- Heat exchanger is removable for improved serviceability. Primary is constructed of aluminized steel, secondary is constructed of stainless steel for maximum corrosion resistance and thermal fatigue reliability.
- Low profile “34 inch” cabinet ideal for space constrained installations.
- Blower Self design – serviceable in all furnace orientations
- Pre marked hoses – insures proper system drainage
- Vent with 2" or 3" PVC
- Replaceable Collector box
- Hemmed edges on cabinet and doors
- Quarter turn fasteners for tool less access
- Integrated control boards feature dip switches for easy system set up
- Self priming condensate trap

### GENERAL TERMS OF LIMITED WARRANTY\*

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Heat Exchanger . . . . .Twenty (20) Years

Conditional Parts  
 (Registration Required) . . . . .Ten (10) Years

†A.F.U.E. (Annual Fuel Utilization Efficiency) calculated in accordance with Department of Energy test procedures.

\*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.

MODEL	INPUT- BTU/HR [kW] ①	HEATING CAPACITY BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
R92PA040	42,000 [12.31]	39,060 [11.45]	1049 [494]	1121 [528]	123.5 [56]	
R92PA060	56,000 [16.41]	52,080 [15.26]	1139 [537]	1232 [581]	128 [58]	
R92PA070	70,000 [20.51]	65,100 [19.67]	1211 [571]	1318 [622]	132 [60]	
R92PA085	84,000 [24.62]	78,120 [22.89]	1704 [804]	1742 [822]	147.5 [67]	
R92PA100	98,000 [38.71]	91,140 [36.00]	1748 [825]	1782 [841]	152 [69]	
R92PA115	112,000 [32.82]	104,160 [30.52]	1750 [825]	1934 [912]	165 [75]	

Note: Above data and specs are for upflow models.

[ ] Designates Metric Conversions





# SALES FACT SHEET

## R92P ACCESSORIES

Description	Part No.	Price
Condensate Pump Kit	1PCB151TUL	
External Bottom Filter (Upflow/Horizontal) Rack	RXGF-CB	
External Side Filter Rack	RXGF-CD	
External Downflow Top Filter Rack	RXGF-CC	
Fossil Fuel Kit	FXPF-F01	
Fossil Fuel Kit	RXPF-F02	
Downflow/Horizontal Conversion Kit	RXGY-CK	
Downflow/Horizontal Left Zero Clearance Conversion Kit	RXGY-ZK	
Combustible Floor Base	RXGC-B17	
Combustible Floor Base	RXGC-B21	
Combustible Floor Base	RXGC-B24	
Direct Vent Furnace Side Wall Vent 2" or 3"	RXGY-G02	
LP Conversion Kit	RXGJ-FP33	
Neutralizer Kit	RXGY-A01	
Return Air Plenum	RXGR-C17B	
Return Air Plenum	RXGR-C21B	
Return Air Plenum	RXGR-B24C	
Vent Termination Kit - Concentric Horizontal/Vertical (US & Canadian Installations) 3" Pipe	RXGY-E03A	
Vent Termination Kit - Concentric Horizontal/Vertical (US & Canadian Installations) 2" Pipe	RXGY-E02A	
Vent Termination Kit - Concentric Horizontal/Vertical (US Installation Only) 2" Pipe	RXGY-E02	
Vent Termination Kit - Concentric Horizontal/Vertical (US Installation Only) 3" Pipe	RXGY-E03	
Indoor Coil Casing	RXBC-D17AI	
Indoor Coil Casing	RXBC-D21AI	
Indoor Coil Casing	RXBC-D24AI	
Indoor Coil Casing	RXBC-D21B1	
Combustible Floor Base	RXGC-B17	
Combustible Floor Base	RXGC-B21	
Combustible Floor Base	RXGC-B24	
Combustion Air Drain Kit 2"	RXGY-D05	
Combustion Air Drain Kit 3"	RXGY-D06	